



JUNCTION BOXES

Trafik (aluzinc casings)



IK08*

Patented



Trafik Mini

Trafik Standard

Junction boxes for traffic or tramway signalling and security cameras or CCTV.

Seamless bent aluzinc junction boxes.

Patented process, 6 times more resistant to corrosion than galvanised sheet.

Plasticised insulating coating offering high-adhesion UV protection that will not separate if scratched.

ADVANTAGES

Numerous inputs-outputs for through and side cables.

Raised terminal block to facilitate connection.

TECHNICAL CHARACTERISTICS

Casing

- Plastic-coated aluzinc (0.35 mm/side).
- Impulse withstand voltage: 4 kV.
- Temperature: -40°C to +115°C.
- Installation standards: NF P99.
- Mounting with lugs, for fastening by strap or connecting strip.

Accepted terminals

- Connection terminals with screwed contacts: D6 (6 mm²), D10 (10 mm²), D16 (16 mm²).
- Spring-loaded, automatic clamping: R2, R4.
- Other products: please contact us.

Max. capacity

Trafik Mini:

- Up to 7 cable inputs-outputs.
- Up to 8 connection terminals.

Trafik Standard:

- Up to 8 cable inputs-outputs.
- Up to 16 connection terminals.

Standard colour:

- Please contact us for other colours.

*Made-to-measure equipment. This equipment has not undergone a standardised certification procedure.

Trafik Mini

- Up to 7 cable inputs-outputs.
- Up to 8 connection terminals (D6).

